

LIGHTING

SERVICE DATA

Headlight relay	3 - 5: 10 k Ω or higher 3 - 5: Below 1 Ω (Battery voltage applied to terminals 1 and 2)
Headlight dimmer relay	3 - 4: Below 1 Ω 3 - 4: 10 k Ω or higher (Battery voltage applied to terminals 1 and 2) 3 - 5: 10 k Ω or higher 3 - 5: Below 1 Ω (Battery voltage applied to terminals 1 and 2)
Taillight relay	3 - 5: 10 k Ω or higher 3 - 5: Below 1 Ω (Battery voltage applied to terminals 1 and 2)
Fog light relay	3 - 5: 10 k Ω or higher 3 - 5: Below 1 Ω (Battery voltage applied to terminals 1 and 2)
Towing tail relay	3 - 5: 10 k Ω or higher 3 - 5: Below 1 Ω (Battery voltage applied to terminals 1 and 2)

SS

TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft.*lbf
Headlight assembly x Front fender panel	2.0	20	17 in.*lbf
Rear combination light assembly x Rear body side panel	5.4	55	48 in.*lbf
Towing converter relay x Body	7.0	71	62 in.*lbf
Wiring harness clamp bracket x Trailer socket	8.3	85	75 in.*lbf
Negative battery terminal x Battery	3.9	40	35 in.*lbf

SS